GP Lighting

Product Data Sheet

GP LD DIM CLS60 14.3-100W E27 W FR

Order code	EAN	Packaging - SKU	
080312-LDCE1	4986149080312	Eco blister, 1 pc/SKU	
Product			
Category		LED Lamps	
Series		CLASSIC - FROSTED	
Model		HI-BRIGHTNESS CLASSIC DIMMABLE	OD
Description		GP LD CLS60 E27 14.3-100W 220-240V FR DIM CE1	GP
		OLI	
General descriptio	n		
Energy label		A+	
.amp shape		Classic A60	
Lamp base		E27	
Dimmable		Yes	
Mercury free		Yes	Ø60
Mercury content		0.0 mg	200
Recycling		Yes	-
Cocyoning		100	-
Electrical characte	ristics		41
Nominal wattage 14.3 W ±10%			
Rated wattage		14.3 W ±1078	
tated wattage Equivalent incandesce	nt lamp power	100 W	
equivalent incandesce	ilit lamp power	>0.7	Spectral Distribution
		220-240 V	Spectral Distribution
Voltage Operating frequency		50/60Hz	1.2
Lamp current		59-65 mA	1.0-
Weighted Energy Consumption		15 KWh / 1000 h	0.8-
weighted Energy Cons	Sumption	13 KWII7 1000 II	
l ight tochnical cha	ractoristics		sbectrar
Light technical characteristics Light colour WARM WHITE			0.4-
Colour temperature		2700 K �270K	0.2-
Colour rendering index	(Pa)	≥80	
Colour consistency	(Na)	<6 SDCM	0.0 380 500 600 700 80 Wavelength (nm)
Nominal luminous flux		1521 lm ±10%	
Rated luminous flux		1521 lm	GP LED Lamps are designed for
Lumen maintenance fa	actor at and of life	≥0.7	true direct replacement of standard
Varm-up time (60%)	icioi al enu oi ille	Instant s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
Starting time		C0.3 S	Very low energy consumption
I ifaanan			Extremely long life
Lifespan Nominal life time		15000 h	Emit a warm white or cold white light
		15000 h 15000 h	for different ambience
Rated lamp life time		15000 h 50000	Instant start with full light output
Switching cycles		50000	
Draduat dimanai			Available in most common lamp bases for household use
Product dimension	15	114 mm \$1 mm	-
Overall length (L)		114 mm �1 mm	• No UV
Diameter (D)		60 mm ♦ 1 mm	Applications
Product Compliance			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications General illumination
Warranty 12 months from ex-factory date			
* Please refer to website www.gp-lighting.com for the list of compatible dimmers.			 Can be used everywhere at home
T lease refer to websi			- I lee outdoore only in sizelessed and
Tiedse refer to websi			Use outdoors only in enclosed and ventilated luminaires

www.gp-lighting.com