GP Lighting

Product Data Sheet

GP LD DIM CLS60 5.4-40W E27 W FM FR

Order code	EAN	Packaging - SKU		
080473-LDCE1	4986149080473	Eco blister, 1 pc/SKU		
Product				
Category		LED Lamps		
Series		VINTAGE CLASSIC		
Selles		- FROSTED (FILAMENT)		
Model		HI-BRIGHTNESS CLASSIC FROSTED-FM		
		DIMMABLE GP LD CLS60 E27 TBA-40W 220-240V FR FM DIM	-	
Description		CE1	CP	
		021		
General descriptio	n			
Energy label		A+		
Lamp shape		Classic A60		
Lamp base		E27		
Dimmable		Yes		
Mercury free		Yes	Ø60±1	
Mercury content		0.0 mg		
Recycling		Yes		
			۲ <u>۲</u>	
Electrical characte	ristics		104+3	
Nominal wattage		5.4 W ±10%		
Rated wattage		5.4 W		
Equivalent incandescent lamp power		40 W		
Power factor		>0.5	Spectral Distribution	
Voltage		220-240 V	1.2	
Operating frequency		50/60Hz	1.2	
Lamp current		22-25 mA	1.0-	
Weighted Energy Consumption		6 KWh / 1000 h	0.8-	
			- II 0.6-	
Light technical cha	aracteristics			
Light colour		WARM WHITE	0.4	
Colour temperature		2700 K ±150K	0.2	
Colour rendering index	(Ra)	≥80	0.0 380 500 600 700 800	
Colour consistency	. ,	<6 SDCM		
Nominal luminous flux		470 lm ±10%		
Rated luminous flux		470 lm	GP LED Lamps are designed for	
Lumen maintenance fa	ctor at end of life	≥0.7	true direct replacement of standard	
Warm-up time (60%)		Instant s	incandescent lamps.	
Starting time		<0.5 s	Compatible shapes and sizes of GLS	
-			 Very low energy consumption 	
Lifespan			Extremely long life	
Nominal life time		15000 h	• Emit a warm white or cold white light	
Rated lamp life time		15000 h	for different ambience	
Switching cycles		50000	Instant start with full light output	
			Available in most common lamp bases	
Product dimensions			for household use	
Overall length (L)		104 mm ±1 mm	• No UV	
Diameter (D)		60 mm ±1 mm	1	
. ,			Applications	
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications	
Varranty 12 months from ex-factory date			General illumination	
* Please refer to website www.gp-lighting.com for the list of compatible dimmers.			Can be used everywhere at home	
* Please refer to webs	no www.gp ngnung.com ic	and a second and a s		
* Please refer to webs	ic www.gp lighting.com ic		-	
* Please refer to webs	ie www.gp iigniing.com ie		Use outdoors only in enclosed and ventilated luminaires	

www.gp-lighting.com