## **GP** Lighting

**Product Data Sheet** 

## Order code Packaging - SKU 084983-LDCF1 4986149084983 Eco blister, 1 pc/SKU Product LED Lamps Category REFLECTOR MR16 (12V) Series - GLASS REFLECTOR Model MR16 GU5.3 DIMMABI F GP LD MR16 GU5.3 4.7-35W 12V 36D DIM Description **General description** Energy label A+ Lamp shape Reflector Lamp base GU5.3 Dimmable Yes Mercury free Yes Mercury content 0.0 mg Recycling Yes **Electrical characteristics** Nominal wattage 4.7 W ±10% Rated wattage 4.7 W 35 W Equivalent halogen lamp power Power factor >0.5 Voltage AC 12V **Spectral Distribution** Operating frequency 50/60Hz Spectrum Lamp current 391 mA Weighted Energy Consumption 6 KWh / 1000 h 1.0 0.8 Light technical characteristics 0.6 Light colour WARM WHITE 0.4 Colour temperature 2700 K ±270K Colour rendering index (Ra) ≥80 Colour consistency <6 SDCM Nominal luminous flux 345 lm ±10% Rated luminous flux 345 lm Rated peak intensity cd GP LED Reflectors are designed Luminous intensity for true direct replacement of standard cd Lumen maintenance factor at end of life ≥0.7 halogen lamps Nominial beam angle 36° • With compatible shapes & sizes 36° • Very low energy consumption Rated beam angle Warm-up time (60%) INSTANT · Extremely long life Starting time <0.5s • Emit a warm white or cold white light for different ambience · Instant start with full light output Lifespan Nominal life time 15000 h No UV 15000 h Rated lamp life time Switching Cycles 50000 **Applications** • Domestic and commercial applications **Product dimensions** General illumination Overall length (L) 46 mm ±1 mm · Can be used everywhere at home Diameter (D) · Use outdoors only in enclosed and 50 mm ±1 mm ventilated luminaires **Product Compliance** CE, ERP, ROHS, REACH 12 months from ex-factory date \* Please refer to website www.gp-lighting.com for the list of compatible transformers.

GP LD MR16 GU5.3 4.7-35W 36D DIM

## www.gp-lighting.com