GP Lighting

Product Data Sheet

GP LD GBM E27 4.5-40W 2-STEP NS CL

Order code	EAN	Packaging - SKU	
085850-LDCE1	4986149085850	Eco blister, 1 pc/SKU	TRUIT
Product			
Category		LED Lamps	
Category		VINTAGE	
Series		- 2-STEP NIGHTSWITCH	
		(FILAMENT)	
Model		MINI GLOBE FILAMENT	
Model		2-STEP NIGHTSWITCH	
Description		GP LD GBM E27 4.5-40W 220-240V 2-STEP	
		NIGHTSWITCH CL	
General description			
Energy label		A++	
Lamp shape		Mini Globe	
Lamp base		E27	
Dimmable		No	
Mercury free		Yes	© 45
Mercury content		0.0 mg	
Recycling		Yes	
Electrical characterist	ics		ge_
Nominal wattage		4.5 W ±10%	
Rated wattage		4.5 W	
Equivalent incandescent lamp power		40 W	
Power factor		0.4	Spectral Distribution
Voltage		220-240 V	
Operating frequency		50/60Hz	Spectrum 1.0=18.737mW/nm 1.2
Lamp current		33.3-40.7 mA	1.0-
Weighted Energy Consumption		5 KWh / 1000 h	0.8-
Weighted Energy Consum	ption	3 KWII7 1000 II	-
Light technical charac	torictics		0.6-
Light technical characteristics Light colour		WARM WHITE	0.4-
		2700 K ±150K	0.2-
Colour temperature	۸	≥80	
Colour rendering index (Ra	1)	<6 SDCM	0.0 350 513 675 838 1000 Wavelength(nm)
Colour consistency			
Nominal luminous flux		470 lm ±10%	CD LED Lamma and 1
Rated luminous flux		470 lm	GP LED Lamps are designed for
Lumen maintenance factor	at end of life	≥0.7	true direct replacement of standard
Warm-up time (60%)		<0.5s	incandescent lamps.
Starting time		Instant	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		20000	Instant start with full light output
			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		78 mm ±2 mm	• No UV
Diameter (D)		45 mm ±1 mm	
. ,		·	Applications
Product Compliance CE, ERP, ROHS, REACH		Domestic and commercial applications	
Warranty		12 months from ex-factory date	General illumination
		. 2orano nom ox ractory date	Can be used everywhere at home
			Use outdoors only in enclosed and
			ventilated luminaires
			ventilated idminiaries

www.gp-lighting.com