GP Lighting

Product Data Sheet

GP LD GBM E14 1.2-15W CL FM

| Order code | EAN | Packaging - SKU | |
|------------------------------------|---------------------|--|--|
| 086390-LDCE1 | 4986149086390 | Eco blister, 1 pc/SKU | |
| | | | |
| | | | |
| | | | |
| | | | |
| Product | | | |
| Category | | LED Lamps | |
| Series | | VINTAGE MINI GLOBE | |
| Model | | - CLEAR (FILAMENT) MINI GLOBE FILAMENT CLEAR | |
| Model Description | | GP LD GBM E14 1.2-15W 220-240V CL FM | |
| 2000.19110.11 | | 9. 25 652 | |
| General description | 1 | | |
| Energy label | | A++ | |
| Lamp shape | | Globe | [三要] |
| Lamp base | | E14 | |
| Dimmable | | No | |
| Mercury free | | Yes | Ø45 |
| Mercury content | | 0.0 mg | |
| Recycling | | Yes | |
| | | | |
| Electrical character | ristics | | <u></u> |
| Nominal wattage | | 1.2 W ±10% | |
| Rated wattage | | 1.2 W | |
| Equivalent incandescent lamp power | | 15 W | |
| Power factor | | / | Spectral Distribution |
| Voltage | | 220-240 V | |
| Operating frequency | | 50/60Hz | Spectrum |
| Lamp current | | 5-15 mA | 1.2 |
| Weighted Energy Consumption | | 2 KWh / 1000 h | 1.0- |
| | | | 0.8- |
| Light technical characteristics | | | 0.6- |
| Light colour | | WARM WHITE | 0.4- |
| Colour temperature | | 2700 K ±270K | 0.2- |
| Colour rendering index | (Ra) | ≥80 | 0.0 380 480 580 680 780 Wavelength(nm) |
| Colour consistency | | <6 SDCM | |
| Nominal luminous flux | | 140 lm ±10% | |
| Rated luminous flux | | 140 lm | GP LED Lamps are designed for |
| Lumen maintenance fa | ctor at end of life | ≥0.7 | true direct replacement of standard |
| Warm-up time (60%) | | INSTANT | incandescent lamps. |
| Starting time | | <0.5s | Compatible shapes and sizes of GLS |
| | | | Very low energy consumption |
| Lifespan | | 450001 | • Extremely long life |
| Nominal life time | | 15000 h | Emit a warm white or cold white light |
| Rated lamp life time | | 15000 h | for different ambience |
| Switching cycles | | 50000 | Instant start with full light output |
| Due donat dimensi : | | | Available in most common lamp bases |
| Product dimension | 5 | 79 mm ±1 mm | for household use |
| Overall length (L) | | 79 mm ±1 mm 45 mm ±1 mm | • No UV |
| Diameter (D) | | 40 mm ±1 mm | Applications |
| Product Compliance | | CE ERD ROHS DEACH | Applications Domestic and commercial applications |
| Warranty | | CE, ERP, ROHS, REACH | Domestic and commercial applications General illumination |
| vvalidiity | | 12 months from ex-factory date | |
| | | | Can be used everywhere at home Use outdoors only in enclosed and |
| | | | - Obe outdoors only in enclosed and |
| | | | ventilated luminaires |

www.gp-lighting.com