GP Lighting

Product Data Sheet GP LD GU10 4.5-50W FD DIM Order code Packaging - SKU Eco blister, 1 pc/SKU 087458-LDCE1 4895149087458 **Product** LED Lamps Category VINTAGE Series - DIM-TO-WARM REFLECTOR GU10 Model FI AMEDIM GP LD TWIST GU10 4.5-50W 220-240V 36D Description FLAMEDIM **General description** Energy label A+ Lamp shape Reflector Lamp base GU10 Dimmable Yes Mercury free Yes Ø50+0.5 Mercury content 0.0 mg Recycling Yes **Electrical characteristics** 24±1.5 4.5 W ±10% Nominal wattage Rated wattage 4.5 W Equivalent halogen lamp power 50 W Power factor >0.5 Voltage Spectral Distribution 220-240 V Operating frequency 50/60Hz Lamp current 18-21 mA Weighted Energy Consumption 5 KWh / 1000 h 0.8 Light technical characteristics WARM WHITE - EXTRA WARM WHITE Light colour 0.4 2700K-1800K K ±145-±180KK Colour temperature Colour rendering index (Ra) ≥80 Colour consistency <6 SDCM Nominal luminous flux 345 lm ±10% Rated luminous flux 345 lm Rated peak intensity GP LED Reflectors are designed cd Luminous intensity cd for true direct replacement of standard Lumen maintenance factor at end of life ≥0.8 halogen lamps. Nominlal beam angle 36° • With compatible shapes & sizes Rated beam angle 36° · Very low energy consumption Warm-up time (60%) <2.0s · Extremely long life • Emit a warm white or cold white light Starting time <0.5s for different ambience Lifespan · Instant start with full light output Nominal life time 15000 h No UV Rated lamp life time 15000 h Switching Cycles 30000 **Applications** · Domestic and commercial applications **Product dimensions** General illumination 54 mm ±2 mm Overall length (L) · Can be used everywhere at home Diameter (D) 50 mm ±1 mm · Use outdoors only in enclosed and ventilated luminaires **Product Compliance** CE, ERP, ROHS, REACH Warranty 12 months from ex-factory date * Please refer to website www.gp-lighting.com for the list of compatible dimmers.

www.gp-lighting.com