GP Lighting

Product Data Sheet

GP LD CLS60 5.7-40W E27 W FR

Order code	EAN	Packaging - SKU	
777930-LDCE1	4986149777930	Eco blister, 1 pc/SKU	
Product			
Category LED Lamps			
Series		CLASSIC - FROSTED	
Model		HI-BRIGHTNESS CLASSIC	
Description		GP LD CLS60 E27 5.7-40W 220-240V FR CE1	GP
			OF-
General descriptior	1		and the second se
Energy label		A+	
Lamp shape		Classic A60	
Lamp base		E27	×
Dimmable		No	
Mercury free		Yes	Ø60
Mercury content		0.0 mg	
Recycling		Yes	
			 _
Electrical character	istics		Ê
Nominal wattage		5.7 W ±10%	
Rated wattage		5.7 W	
Equivalent incandescer	nt lamp power	40 W	
Power factor		>0.5	Spectral Distribution
Voltage		220-240 V	1.2.
Operating frequency		50/60Hz	1.2
Lamp current		23-26 mA	1.0-
Weighted Energy Consumption		6 KWh / 1000 h	0.8-
3			
Light technical cha	racteristics		10.6- 6
Light colour		WARM WHITE	0.4-
Colour temperature		2700 K ±270K	0.2-
Colour rendering index	(Ra)	≥80	
Colour consistency	()	<6 SDCM	0.0 380 500 600 700 Wavelength (nm)
Nominal luminous flux		470 lm ±10%	
Rated luminous flux		470 lm	GP LED Lamps are designed for
Lumen maintenance factor at end of life Warm-up time (60%)		≥0.7	true direct replacement of standard
		Instant s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Externely long life Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
•			
Switching cycles		50000	Instant start with full light output
Dreduct dimension	-		Available in most common lamp bases
Product dimensions		100	for household use
Overall length (L)		109 mm ±1 mm	• No UV
Diameter (D)		60 mm ±1 mm	
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
			Can be used everywhere at home
			 Can be used everywhere at home Use outdoors only in enclosed and

www.gp-lighting.com