GP Lighting

Product Data Sheet

GP LD CDM 3.5-25W E14 W FR

Order code	EAN	Packaging - SKU	
777992-LDCE1	4986149777992	Eco blister, 1 pc/SKU	
Product			
Category LED Lamps			
		DECORATIVE CANDLE	
Series		- FROSTED	
Model		DECO MINI CANDLE FROSTED	CD
Description		GP LD CDM E14 3.5-25W 220-240V FR CE1	GP
General description			
Energy label		A+	1.50
Lamp shape		Candle	
Lamp base		E14	
Dimmable		No	
Mercury free		Yes	Ø35
Mercury content		0.0 mg	
Recycling		Yes	
			E
Electrical character	istics		[] [] [] [] [] [] [] [] [] [] [] [] [] [
Nominal wattage 3.5 W ±10%			
Rated wattage		3.5 W	
Equivalent incandescent lamp power		25 W	
Power factor		>0.5	Spectral Distribution
Voltage		220-240 V	1.2
Operating frequency		50/60Hz	
Lamp current		14-16 mA	1.0-
Weighted Energy Consumption		4 KWh / 1000 h	0.8-
0,0,			- 6-0 gitt
Light technical char	racteristics		
Light colour		WARM WHITE	0.4-
Colour temperature		2700 K ±270K	0.2
Colour rendering index (Ra)		≥80	0.0 360 500 600 700 800
Colour consistency		<6 SDCM	380 500 600 700 800 Wavelength (nm)
Nominal luminous flux		250 lm ±10%	
Rated luminous flux		250 lm	GP LED Lamps are designed for
Lumen maintenance fa	ctor at end of life	≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	Instant start with full light output
Ownerning cycles		30000	Available in most common lamp bases
Product dimensions			for household use
Overall length (L)	3	105 mm ±1 mm	No UV
5 ()		35 mm ±1 mm	
Diameter (D)		35 mm ±1 mm	Applications
Product Complian -		CE EDD DOUG DEACU	Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
			Can be used everywhere at home
			 Use outdoors only in enclosed and
			ventilated luminaires

www.gp-lighting.com