GP Lighting

Product Data Sheet

GP LD DIM CDM 6-40W E14 W FR

Order code	EAN	Packaging - SKU	
778050-LDCE1	4986149778050	Eco blister, 1 pc/SKU	
Product			
Category		LED Lamps	
		DECORATIVE CANDLE	
Series		- FROSTED	
Model		DECO MINI CANDLE FROSTED DIMMABLE	
Description		GP LD CDM E14 6-40W 220-240V FR DIM CE1	GP
General descriptio	n		
Energy label		A+	5.87
_amp shape		Candle	3
Lamp base		E14	3
Dimmable		Yes	
Mercury free		Yes	Ø3 <u>5</u>
Mercury content		0.0 mg	
Recycling		Yes	7 / 1
			107
Electrical characte	ristics		
Nominal wattage		6 W ±10%	
Rated wattage		6 W	_
Equivalent incandesce	nt lamp power	40 W	
Power factor		>0.8	Spectral Distribution
Voltage		220-240 V	1.2
Operating frequency		50/60Hz	1.0-
Lamp current		25-28 mA	
Weighted Energy Con-	sumption	6 KWh / 1000 h	0.8- g
Light technical cha	ractoristics		20.6-
Light technical characteristics Light colour		WARM WHITE	0.4-
Colour temperature		2700 K ±270K	0.2
Colour rendering index	(Ra)	≥80	
Colour consistency	ι (κα)	<6 SDCM	0.0 380 500 600 700 800 Wavelength (nm)
Nominal luminous flux		470 lm ±10%	
Rated luminous flux		470 lm	GP LED Lamps are designed for
Lumen maintenance fa	actor at end of life	≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
<u> </u>			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	Instant start with full light output
			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		107 mm ±1 mm	• No UV
Diameter (D)		35 mm ±1 mm	.
Product Compliance		CE ERP ROHS REACH	Applications Domestic and commercial applications
Product Compliance Warranty		CE, ERP, ROHS, REACH 12 months from ex-factory date	Domestic and commercial applications General illumination
* Please refer to website www.gp-lighting.com for the list of compatible dimmers.			Can be used everywhere at home
. 1929 1937 to mosolic minings lighting both for the list of compatible diffillers.			Use outdoors only in enclosed and
			ventilated luminaires
			vendiated iditilialies

www.gp-lighting.com