GP Lighting

Product Data Sheet

GP LD ST64 4.6-34W E27 EW FM GD

Order code	EAN	Packaging - SKU	
080664-LDCE1	49861490	Eco blister, 1 pc/SKU	
Product			
Category		LED Lamps	
		VINTAGE ST64	
Series		- GOLD (FILAMENT)	F
Model		DECO ST64 GOLD-FM	
Description		GP LD ST64 E27 4.6-34W 220-240V GD FM CE1	
•			
General descriptio	n	A .	
Energy label		A+	
Lamp shape		ST64	
Lamp base		E27	
Dimmable Mercupy free		No	#65±1
Mercury free		Yes	
Mercury content		0.0 mg	
Recycling		Yes	
Electric et al.			
Electrical characte	eristics		
Nominal wattage		4.6 W ±10%	
Rated wattage		4.6 W	
Equivalent incandesce	ent lamp power	34 W	
Power factor		>0.4	Spectral Distribution
Voltage		220-240 V	1.2
Operating frequency		50/60Hz	1.0-
Lamp current		19-21 mA	
Weighted Energy Consumption		5 KWh / 1000 h	- g
Light technical cha	aracteristics		0.4
Light colour		WARM WHITE	
Colour temperature		2500 K ±250K	0.2-
Colour rendering index	k (Ra)	≥80	0.0 380 500 600 700 800 Wavelength (nm)
Colour consistency		<6 SDCM	Wavelength (nm)
Nominal luminous flux		380 lm ±10%	
Rated luminous flux		380 lm	GP LED Lamps are designed for
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan		120001	• Extremely long life
Nominal life time		15000 h	• Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	Instant start with full light output
			Available in most common lamp bases
Product dimension	าร		for household use
Overall length (L)		140 mm ±1 mm	• No UV
Diameter (D)		64 mm ±1 mm	
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	General illumination
			 Can be used everywhere at home
			Use outdoors only in enclosed and
			 Use outdoors only in enclosed and ventilated luminaires

www.gp-lighting.com