GP Lighting

Product Data Sheet

GP LD CLS60 E27 5-13W SMK SPFM

Order code	EAN	Packaging - SKU	
085706-LDCE1	4986149085706	Eco blister, 1 pc/SKU	10-
Product			
Category		LED Lamps	
Series		VINTAGE	
		- SMOKE LAMP	
		(SPIRAL FILAMENT)	
Model		CLASSIC FILAMENT SMOKED GLASS SPIRAL	
Description		GP LD CLS60 E27 5-13W 220-240V SMK SPFM	
General description			
Energy label		В	
Lamp shape		Classic A60	
Lamp base		E27	
Dimmable		No	
Mercury free		Yes	440
Mercury content		0.0 mg	
Recycling		Yes	
. 5			
Electrical characteris	tics		ă
Nominal wattage		5 W 10	
Rated wattage		5 W	
Equivalent incandescent lamp power		13 W	
Power factor		0.5	Spectral Distribution
Voltage		220-240 V	Spectrum 1.0=2.412mW/nm
Operating frequency		50/60Hz	1.2
Lamp current		32.4-48.4 mA	1.0-
Weighted Energy Consumption		5 KWh / 1000 h	0.8
			0.6-
Light technical charac	cteristics		
Light colour		EXTRA WARM WHITE	0.4
Colour temperature		1800 K /K	0.2
Colour rendering index (Ra)		≥80	0.0 350 513 675 838 1000
Colour consistency		<6 SDCM	350 513 6/5 838 1000 Wavelength(nm)
Nominal luminous flux		120 lm ±10%	
Rated luminous flux		120 lm	GP LED Lamps are designed for
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard
Warm-up time (60%)		<1s	incandescent lamps.
Starting time		Instant	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		20000	Instant start with full light output
			Available in most common lamp bases
Product dimensions			for household use
Overall length (L)		104 mm ±2 mm	• No UV
Diameter (D)		60 mm ±1 mm	
			Applications
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Warranty		12 months from ex-factory date	This lamp is intended to change the
			appearance of the scene.
			It is not suitable for household illumination.
			Use outdoors only in enclosed and

www.gp-lighting.com