## **GP** Lighting

## **Product Data Sheet**

## GP LD ST26 E14 2.5-25W CL

Order code	EAN	Packaging - SKU		
085942-LDCE1	4986149085942	Eco blister, 1 pc/SKU	4	
Product				
Category		LED Lamps		
Series		VINTAGE ST26 - (FILAMENT)	19	
Model		ST26 FILAMENT CLEAR		
Description		GP LD ST26 E14 2.5-25W 220-240V CL		
General description	on			
Energy label		A++		
Lamp shape		ST26		
Lamp base		E14		
Dimmable		No	φ26	
Mercury free		Yes	- W20	
Mercury content		0.0 mg		
Recycling		Yes		
Florida del construitation				
Electrical characteristics				
Nominal wattage		2.5 W ±10%		
Rated wattage		2.5 W		
Equivalent incandescent lamp power		25 W	Spectral Distribution	
Power factor		0.4	Spectral Distribution	
Voltage Operating frequency		220-240 V 50/60Hz	Spectrum 1.0-18.737mW/nm	
Lamp current		17.1-20.9 mA	1.0-	
Weighted Energy Consumption		3 KWh / 1000 h		
vveignited Energy Cor	isumption	3 KWII7 1000 II	0.8-	
Light technical characteristics			0.6-	
Light colour		WARM WHITE	0.4-	
Colour temperature		2700 K ±150K	0.2-	
Colour rendering inde	x (Ra)	≥80	0.0350 513 675 838 1000	
Colour consistency	( ' ' )	<6 SDCM	350 513 675 838 1000 Wavelength(nm)	
Nominal luminous flux	(	250 lm ±10%		
Rated luminous flux		250 lm	GP LED Lamps are designed for	
Lumen maintenance factor at end of life		≥0.7	true direct replacement of standard	
Warm-up time (60%)		<0.5s	incandescent lamps.	
Starting time		Instant	Compatible shapes and sizes of GLS	
			Very low energy consumption	
Lifespan			Extremely long life	
Nominal life time		15000 h	Emit a warm white or cold white light	
Rated lamp life time		15000 h	for different ambience	
Switching cycles		20000	Instant start with full light output	
		Available in most common lamp bases		
Product dimensions		for household use		
Overall length (L)		61 mm ±2 mm	• No UV	
Diameter (D)		26 mm ±1 mm		
			Applications	
Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications	
Warranty		12 months from ex-factory date	General illumination	
			Can be used everywhere at home	
			Use outdoors only in enclosed and	
			ventilated luminaires	

## www.gp-lighting.com