## **GP** Lighting

## Product Data Sheet

## GP LD CLS60 9.4-60W E27 W FR

Order code	EAN	Packaging - SKU	
777954-LDCE1	4986149777954	Eco blister, 1 pc/SKU	
781104-LDCE1	4986149781104	Eco blister, 1 pc/SKU	
Product			
Category		LED Lamps	
Series		CLASSIC - FROSTED	
Model		HI-BRIGHTNESS CLASSIC	
Description		GP LD CLS60 E27 9.4-60W 220-240V FR CE1	GP
General description	n		
Energy label		A+	
Lamp shape		Classic A60	
Lamp base		E27	
Dimmable		No	
Mercury free		Yes	Ø60
Mercury content		0.0 mg	
Recycling		Yes	
, ,			9
Electrical characte	ristics		8
Nominal wattage		9.4 W ±10%	
Rated wattage		9.4 W	•
Equivalent incandesce	nt lamp power	60 W	
Power factor		>0.5	Spectral Distribution
Voltage		220-240 V	1.27
Operating frequency		50/60Hz	
Lamp current		39-43 mA	1.0-
Weighted Energy Cons	sumption	10 KWh / 1000 h	0.8-
0 0,			0.6 -
Light technical cha	racteristics		
Light colour		WARM WHITE	0.4-
Colour temperature		2700 K ±270K	0.2-
Colour rendering index	(Ra)	≥80	0.0 500 600 700 800
Colour consistency		<6 SDCM	380 500 600 700 800 Wavelength (nm)
Nominal luminous flux		806 lm ±10%	
Rated luminous flux		806 lm	GP LED Lamps are designed for
Lumen maintenance fa	actor at end of life	≥0.7	true direct replacement of standard
Warm-up time (60%)		Instant s	incandescent lamps.
Starting time		<0.5 s	Compatible shapes and sizes of GLS
			Very low energy consumption
Lifespan			Extremely long life
Nominal life time		15000 h	Emit a warm white or cold white light
Rated lamp life time		15000 h	for different ambience
Switching cycles		50000	Instant start with full light output
		-	Available in most common lamp bases
	s	for household use	
Product dimension		109 mm ±1 mm	• No UV
Product dimension Overall length (L)		00 4	
		60 mm ±1 mm	
Overall length (L) Diameter (D)			Applications
Overall length (L) Diameter (D)  Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications
Overall length (L) Diameter (D)			Domestic and commercial applications     General illumination
Overall length (L) Diameter (D)  Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications     General illumination     Can be used everywhere at home
Overall length (L) Diameter (D)  Product Compliance		CE, ERP, ROHS, REACH	Domestic and commercial applications     General illumination

## www.gp-lighting.com